## IN THE CLAIMS:

- 1. (Currently Amended) Urinal comprising a dish (10), which forms a urinal basin (12) having a bottom and a drain passage (26) in its the bottom, and syphon trap (20) connected to the drain passage, (26) characterised in that wherein the dish (10) forms an essentially vertical wall (12) which separates the urinal basin (14) from a chamber (18) arranged behind the same, and in that the syphon trap (20) is arranged to be accessible from above in the chamber (18).
- 2. (Currently Amended) Urinal according to claim 1, characterised in that wherein the wall (12) has, in plan view, a convex shape bulging into the urinal basin.
- 3. (Currently Amended) Urinal according to claim 2, characterised that wherein the chamber (18) is closed at its top end by a detachable lid (22).
- 4. (Currently Amended) Urinal according to claim 2 or 3, characterised in that wherein the lid (10) is adapted to be mounted to a <u>building</u> wall such that the vertical edges of the curved vertical wall (12) engage a the building wall (16), the top and/or lower edges of the vertical wall (12) are beveled such that the chamber (18) tapers towards the front, and in that the lower opening of the chamber (18) is closed by a detachable lid (24).
- 5. (Currently Amended) Urinal according to claim 1 any of the preceeding claims, characterised in that wherein the syphon trap (20) is a waterless syphon trap.
- 6. (Currently Amended) Urinal according to claim 5, eharacterised in that wherein the syphon trap (20) is detachably, but fluid-tightly, inserted into an intermediate floor (30) which, together with a rear wall (31) and the vertical wall (12), forms a tub that extends higher than the edge of the urinal basin (14).
- 7. (Currently Amended) Urinal according to claim 5 or 6, characterised in that wherein the syphon trap (20) has a forced ventilation valve (50).

- 8. (Currently Amended) Urinal according to <u>claim 5</u> any of the claims 5 to 7, eharacterised in that <u>wherein</u> a storage tank (54) for liquid and a dosage system (56, 58) for automatically dosing liquid into the syphon trap (20) are arranged in the chamber (18).
- 9. (Currently Amended) Urinal according to claim 5 any of the claims 5 to 8, eharacterised in that wherein the syphon trap (20) contains a trap liquid (F) to which a scent agent has been added.
- 10. (Currently Amended) Urinal according to <u>claim 5</u> any of the claims 5 to 9, characterised by <u>comprising</u> a key (62) adapted to be locked to the syphon trap (20), a top end of the key being connected to a lever (66) through a joint (64), and the key being so dimensioned that the lever (66) can be supported on the top edge of the vertical wall (12) of the dish (10), in order to lift the syphon trap (20) or a cover thereof upwardly by lever action.
- 11. **(New)** Urinal according to claim 5, comprising a key adapted to be locked to the syphon trap, a top end of the key being connected to a lever through a joint, the key being so dimensioned that the lever can be supported on the top edge of the vertical wall of the dish, in order to lift a cover of the syphon trap upwardly by lever action.